

Specification**Code-Nr.: C171710****Photos****Electrical properties**

| | |
|-----------------|---------------------------------|
| Antenna Type | Directive Antenna |
| Frequency range | 890 ÷ 960 MHz |
| GSM-ETACS-NNT | 1710 ÷ 1880 MHz |
| PCN-GSM | 1920 ÷ 1990 MHz (uplink tr.) |
| UMTS | 2110 ÷ 2170 MHz (downlink ric.) |
| | 1900 ÷ 1920 MHz (uplink tr.) |
| | 2010 ÷ 2025 MHz (downlink ric.) |
| Impedance | 50 Ohm |
| Max Power | 50 Watt |
| V.S.W.R. | 900 MHz less than 1.5 |
| | 1800 MHz less than 2.0 |
| Polarization | Vertical |
| Emission | Directive |
| Gain | 12 dBi |

Mechanical properties

| | |
|-----------------|--|
| Material | Aluminium + schock-resistent Polystyrene |
| Colour | Grey |
| Net weight | 450 g |
| Dimension | 230*170*70 mm |
| Wind resistance | 120 Km/h |
| Mounting | On pale (from Ø20mm ÷ Ø55mm) |
| Temperature | -30°C - +80°C |
| Connector | Panel N female |

EIGENSCHAFTEN TITEL

Diagrams
